DATASHEET

UNV 2.0MP TVI Varifocal Bullet(Metal,OSD,2.8-12mm,IR)

CAM212LR1-Z28



Key Features

- 2 Megapixel high-performance CMOS;
- Analog HD output, up to 2MP resolution;
- Day/night functionality;
- Lowlight surveillance;
- 2.8~12 mm vari-focal lens;
- Up to 20m (98 ft) IR distance;
- OSD menu Cable;
- IP66;

Specifications

Camera	CAM212LR1-Z28
Sensor	1/2.7", 2.0 megapixel, progressive scan CMOS
Signal System	PAL or NTSC
Max. Resolution	1920×1080
Zoom/Focus	Manual
Min. Illumination	Color: 0.1Lux @(F1.2,AGC ON),0 LUX with IR B&W: 0.01 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s to 1/10,000s
Day and Night Function	Support IR-cut
Lens Parameters	Φ14
Lens Type	2.8-12mm
Video output	1Vp-p Composite Output(75Ω/BNC)
Power	DC12V±10%
Dimensions (Ø x H)	268.2mm x Φ90.68mm
Weight	1190g
Working Environment	-10°C ~ +60°C, Humidity ≤ 90% RH(non-condensing)
Ingress Protection	IP65

Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China (310051)

Email：overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2015 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.